



Fonalfeldolgozó és Műszakiszövet-gyártó Bt. H-7130 Tolna, Bezerédj Pál tér 1. Pf.:33

Tel.: (00 36) 74/540-200

Fax: (00 36) 74/540-243

E-mail:info@tolnatext.hu

Performance Declaration No. TNYE00013/2013

- 1. Unique identification code of the product type: 41-345
- 2. Intended purpose of the product:

Glass fabric meshes can be applied for the strengthening of plasters in outdoor and indoor environments generally.

3. Name and address of the manufacturer:

Tolnatext Fonalfeldolgozó és Műszakiszövet-gyártó Bt, 7130 Tolna, Bezerédj tér 1.

4. Name and postal address of authorised representative:

Pilisiné Borza Klára 7130 Tolna, Bezerédj tér 1.

5. The system or systems used for the assessment and verification of the constancy of construction products' performance, according to those included in Attachment V:

System 4 (ÉMI)

2+ WIEN ZERT

6. The manufacturer's declaration was prepared on the basis of the Construction Product Technical Approval (ÉME) No. A-190/2001. issued by ÉMI NON-PROFIT COMPANY FOR QUALITY CONTROL AND INNOVATION IN BUILDING.

The method of certifying product compliance was according to the joint decree No. 3/2003 (I.25.) of BM-GKM-KvVM Annex 4 System (4) and based on ETAG 004 guidelines.

Based on the 2+ compliance certification system it is certified by certification No. 0035/04 on our factory production control issued by Amt der Wiener Landesregierung- Zertifizierungsstelle für Bauprodukte WIEN ZERT.

7. Performance according to the declaration:

| Basic properties | Performance | | Harmonised technical regulations (test method) |
|--|----------------------------------|----|--|
| Safety of use: Tensile strength in warp/weft direction | warp>= 40 N/mm weft>= 40 N/mm | | ETAG 004 5.6.7.1 |
| Durability Tensile strength after alkaline storage for 28 days at room temperature | warp:>=20 N/mm weft:>=15 N/mm | n. | ETAG 004 5.6.7.1 |

| Other characteristics: | | | |
|------------------------------|------------|---------------------|--|
| - number of threads 1/10 cm, | 8/7 | | |
| warp/weft | | | |
| - mesh size (mm) | 11,8/12,4 | | |
| - thickness (mm) | 0,5-0,8 | | |
| - weight per sq. m. (g/m2) | >=110 g/m2 | ETAG 004 item C.6.1 | |

8. The performance of the product specified in clause 1 corresponds to the performance indicated in clause 7, according to the declaration.

The manufacturer specified in clause 3 is solely responsible for issuing the present performance declaration.

TOLNATEXT Fondfeldolgozó és

TOLNATEXT Fondfeldolgozó és

TNűszakiszövet-gyártó Bt.

7130 TOLNA, Bezerédl F. tér 1. Pf.: 3:

Tel.: 74/540-200 Telefaxi 74/540-24:

Tel.: 74/540-200 Telefaxi 74/540-24:

The person signing for and on behalf of the manufacturer:

Pilisiné Borza Klára

Quality Manager

Tolna, 01-07-2013